

## WT-GLED-8620-4K-CMS 86" Interactive Collaboration Display

The 86" collaboration display has everything built in for collaboration. Ideal for meeting rooms for collaboration and interactivity. Built-in Camera, Speakers and Microphone support cloud based VC Such as Zoom and Teams. The built in interactive displays helps for in room collaboration with multiple users able to work with the display at the same time. Ideal for Teaching and Learning environment.

## **Key Features**

- Ultra HD Resolution (4K)
- 20 point touch
- Built in Camera, Mic, Speakers-for collaboration
- Built in PIP (picture in Picture)
- USB C interface

ideate . create . collaborate



LCD Specification  Screen Size(Diag.)  86"  2840 x 2160	
( 3 /	
Posalution 3940 x 2160	
Resolution 3840 x 2160	
Frame Rate 60	
Brightness 350cd/m²	
Aspect Ratio 16:9	
Contrast Ratio 4000:1	
Viewing Angle(H/V) 178°	
Response Time(G to G) 8ms	
Backlight Unit D-LED	
Display Color 10bit(D),1.07Billioncolors	
Backlight Life 50,000Hours	
Touch Technology	
Touch Technology Infrared Touch	
Touch Point 20pt	
Accuracy Φ 2mm	
Resolution 32767 x 32767	
Response Time(G to G) ≤6ms	
Response Time(G to G) ≤6ms  Operation System Windows, Mac, Android, Linux	
Operation System Windows, Mac, Android, Linux	
Operation System Windows, Mac, Android, Linux Camera	
Operation System Windows, Mac, Android, Linux  Camera  12MP	
Operation System Windows, Mac, Android, Linux  Camera Camera 12MP  Microphone 6 Arrays	
Operation System Windows, Mac, Android, Linux  Camera Camera 12MP  Microphone 6 Arrays  Speaker	
Operation System Windows, Mac, Android, Linux  Camera 12MP  Microphone 6 Arrays  Speaker  Speaker 15W x2	
Operation System Windows, Mac, Android, Linux  Camera  Camera 12MP  Microphone 6 Arrays  Speaker  Speaker 15W x2  Connectivity (Input)	
Operation System Windows, Mac, Android, Linux  Camera  Camera 12MP  Microphone 6 Arrays  Speaker  Speaker 15W x2  Connectivity (Input)  Video(analogue) VGA x1	
Operation System Windows, Mac, Android, Linux  Camera 12MP Microphone 6 Arrays  Speaker Speaker 15W x2  Connectivity (Input)  Video(analogue) VGA x1  Video(Digital) HDMI x3	
Operation System Windows, Mac, Android, Linux  Camera  Camera 12MP  Microphone 6 Arrays  Speaker  Speaker 15W x2  Connectivity (Input)  Video(analogue) VGA x1  Video(Digital) HDMI x3  Audio Mic(3.5mm) x1, Audio x1	
Operation System  Windows, Mac, Android, Linux  Camera  12MP  Microphone 6 Arrays  Speaker  Speaker 15W x2  Connectivity (Input)  Video(analogue) VGA x1  Video(Digital)  HDMI x3  Audio Mic(3.5mm) x1, Audio x1  Touch  Windows, Mac, Android, Linux  Valey  Touch USB type-B x2	
Operation System  Windows, Mac, Android, Linux  Camera  12MP  Microphone 6 Arrays  Speaker  Speaker 15W x2  Connectivity (Input)  Video(analogue) VGA x1  Video(Digital)  HDMI x3  Audio Mic(3.5mm) x1, Audio x1  Touch USB type-B x2  Media  USB 2.0 x3	
Operation System Windows, Mac, Android, Linux  Camera  Camera 12MP  Microphone 6 Arrays  Speaker  Speaker 15W x2  Connectivity (Input)  Video(analogue) VGA x1  Video(Digital) HDMI x3  Audio Mic(3.5mm) x1, Audio x1  Touch USB type-B x2  Media USB 2.0 x3  LAN RJ45(10/100MB) x1	
Operation System         Windows, Mac, Android, Linux           Camera         12MP           Microphone         6 Arrays           Speaker         15W x2           Connectivity (Input)         VGA x1           Video(analogue)         VGA x1           Video(Digital)         HDMI x3           Audio         Mic(3.5mm) x1, Audio x1           Touch         USB type-B x2           Media         USB 2.0 x3           LAN         RJ45(10/100MB) x1           Screen Control         RS-232 x1	
Operation System         Windows, Mac, Android, Linux           Camera         12MP           Microphone         6 Arrays           Speaker         15W x2           Connectivity (Input)         VGA x1           Video(analogue)         VGA x1           Video(Digital)         HDMI x3           Audio         Mic(3.5mm) x1, Audio x1           Touch         USB type-B x2           Media         USB 2.0 x3           LAN         RJ45(10/100MB) x1           Screen Control         RS-232 x1           OPS Computer Slot         4K/30HZ	
Operation System         Windows, Mac, Android, Linux           Camera         12MP           Microphone         6 Arrays           Speaker         15W x2           Connectivity (Input)         VGA x1           Video(analogue)         VGA x1           Video(Digital)         HDMI x3           Audio         Mic(3.5mm) x1, Audio x1           Touch         USB type-B x2           Media         USB 2.0 x3           LAN         RJ45(10/100MB) x1           Screen Control         RS-232 x1           OPS Computer Slot         4K/30HZ           Connectivity (Output)	
Operation System  Camera  Camera  12MP  Microphone 6 Arrays  Speaker  Speaker  Speaker  15W x2  Connectivity (Input)  Video(analogue) VGA x1  Video(Digital) HDMI x3  Audio Mic(3.5mm) x1, Audio x1  Touch USB type-B x2  Media USB 2.0 x3  LAN RJ45(10/100MB) x1  Screen Control RS-232 x1  OPS Computer Slot  Connectivity (Output)  Audio  Coax x1	

Android		
System Version	Android 9.0	
CPU	G52	
GPU	A53 x4	
RAM	3GB	
ROM	32GB	
Environmental Conditions		
Operating Temp.	0~45°C	
Operating Humidity	10~90% RH	
Physical Specification (Product)		
Dimension(WxHxD)	1959mm x 1151.74mm x 89.2mm	
VESA	800 x 600mm	
Net Weight	73kg	
Accessories		
Remote Control x1		
Power cord x1		
Quick Start Guide x1		
Stylus x2		
Wall Mount x1		
HDMI 3M x1		